



Modulized Wireless Portable Sound System

General Features

- High efficiency output power with inbuilt mono BTL digital amplifier power stage.
- Truly wireless! Battery operation eliminates all cables so you can take it anywhere!
- All-In-One portable sound system. Easy to operate in both indoors and outdoors
- Excellent aesthetic design built from a patented rugged aluminum enclosure
- Speaker system : 10" full range speaker with maximum output of 150W
- 100-240V AC switch mode power supply
- 24V DC supply by 2 built-in, rechargeable lead-acid batteries
- Charging indicator LED and Smart Charging circuit
- Up to four UHF PLL diversity wireless mic receivers
- RP-6016m/RP-6100m wireless transmitter modules available for longer and wider operating distance.
- 1 XLR / Jack combo connector for wired mic input
- 2 Outputs: LINE OUT \ ACTIVE OUT
- Controls: MIC Input, Line Volume, Bass, Treble, Master Volume
- Line input & outputs via dual RCA jacks
- Voice Priority circuitry automatically ducks music during speech (switchable on/off)
- Integrated preamplifier, mixer and amplifier circuitry
- Individual volume control for wired and wireless microphones.
- Anti-scratch bumper designed to avoid any scratches or marks during transportation
- Integrated retractable handle and wheels for easy portability.
- The CD / USB player can be remotely operated from both front and rear of unit
- Available Versions:
 CD player (USB 2.0) / (USB 2.0 + pitch control)
 DVD player
 Digital recorder player
- Tripod stand mountable with ST-50 (standard) / ST-51 (wind-up)
- New SLAVE can have 1 or 2 receiver modules installed allowing it to function as an independent PA system.
- Wired Audio Link : Up to 20 SLAVE units can be linked through IN / OUT jacks to form a larger wired system.
- Wireless Audio Link : A larger system of multiple SLAVE units can be wirelessly linked using wireless built-in receiver / transmitter modules - no cables or wires at all!



Specifications

| | |
|----------------|--|
| Output power | Max 150W / 120W(RMS) 4Ω load (class-D) |
| Speaker system | 10" full range |
| T.H.D. | < 0.5% |
| Audio input | Mic in, Line in |
| Audio output | Line out, Active out External speaker |
| Power supply | 90-260VAC 30VDC / 4A |
| Battery used | 12V / 5A x2 |
| Operating time | 5-6 hours in music > 10 hours in speech |
| Charging time | about 6 hours |
| Dimension (mm) | 500H, 350W, 300D |
| Weight (kg) | 21 |
| Patent | Taiwan, China, USA, Europe, Australia |
| Approval | CE, RoHS, FCC, ICID |
| Module | SDR-6200m / 6100m / RP-6100m SDR-6216m / 6116m / RP-6016m |
| Freq. response | 50Hz-20KHz ± 3dB |
| Antenna | Built-in |